

Development of the method for estimating the inertia radius relative to the vertical axis of the car

Podrigalo M. A.¹, Korobko A. I.^{2*}, Dubinin E. A.³, Tarasov Yu. V.³, Baytzur M. V.³

¹ Kharkiv P. Vasylenko National Technical University of Agriculture, 44 Alchevskih St., 61002, Kharkiv, Ukraine;

² L. Pogorilyy Ukrainian Scientific Research Institute of Forecasting and Testing of Machinery and Technologies for Agricultural Production, Kharkiv branch, 236 Velyko-Panasivska St., 61139, Kharkiv, Ukraine;

³ Kharkiv National Automobile and Highway University, 25 Yaroslava Mudrogo St., Kharkiv, Ukraine

Article info:

Paper received:

November 4, 2017

The final version of the paper received:

December 3, 2017

Paper accepted online:

December 4, 2017

*Corresponding Author's Address:

ak82andrey@gmail.com

Abstract. The method of estimating the inertia radius relative to the vertical axis of the car is proposed. This allows a third to reduce the relative error of its definition. A refined formula for calculating the radius of inertia design with respect to the vertical axis of the car is proposed. The use of the proposed formula reduces the error of determining the radius of inertia from 21–27 % to 5 %, and the error of determining the inertia moment for the car from 46–61 % to 10 %. A method for assessing the adequacy of the results of theoretical and experimental studies is proposed. The use of the method has shown that the refined formula for calculating the radius of inertia relative to the vertical axis of the car makes it possible to reduce the probability of mismatching the results up to three times.

Keywords: moment of inertia, radius of inertia, error, car, method, methodical error, mismatch of results.

1 Introduction

The inertia moment relative to the vertical axis substantially affects the handling and stability of the car. At the design stage of the car methods for determining the inertia moment relative to the vertical axis not accurate enough. The test stand is difficult to determine the inertia moment need to design. Probabilistic methods to calculate the inertia radius relative to the vertical axis of the car propose by different authors. More than 30 % is error for the probabilistic method. The inertia radius has degree two in the formula the inertia moment.

In this article, a method for estimating the inertia radius relative to the vertical axis of the car was offered. It is based on the results of experimental studies are known. This reduces the methodological error in three times.

The task is to determine the inertia moment relative to the vertical axis for the car in the design phase occurs. The inertia moments and position of centre of mass have a significant effect on stability and handling for the car. The center of mass is characterized by horizontal coordinates and vertical coordinates of the car. The coordinates of the center of mass in the design are determined by graphical and analytical method.

The essence of the method. The essence of the method. Find on the drawing the relative position of the center of mass for each unit or item of the car. To find its distance to a particular axis. Find its distance to a particular axis. The horizontal coordinate b for the center of mass of the car (from rear axle) can be found by the following formula:

$$b = \frac{G_1x_1 + G_2x_2 + G_3x_3 + \dots + G_nx_n}{G_a} = \sum_{i=1}^n q_i x_i \quad (1)$$

where G_a – the weight of the car, N; G_1, G_2, G_3, G_i – the weight individual components of car that, are used in the determination of the position of its center of mass; q_i – the relative weight of the i -th unit;

$$q_i = \frac{G_i}{G_a} \quad (2)$$

x_1, x_2, x_3, x_i – the shoulders of the moments of forces of attraction for the elements of the car relative, to the rear axle; n – the number of elements which are taken into account when calculating the center of mass of the last.

The location of the other centre of mass for the car is determined similarly.

The question arises. Graphical and analytical method is used to assess the inertia moment relative to the vertical axis of the car.

The obvious is that

$$\sum_{i=1}^n G_i (x_i - b) = 0 \quad (3)$$

The inertia moment relative to the vertical axis of the car is found as

$$I_{cz} = \sum_{i=1}^n \frac{G_i}{g} (x_i - b)^2 + \sum_{i=1}^n \frac{G_i}{g} i_{zi}^2 \quad (4)$$

where i_{zi} – the inertia radius relative to the vertical axis of the car the i -th element, m; g – acceleration of gravity, $g = 9,81 \text{ m/s}^2$.

It is impossible to determine I_{zc} using the graphical and analytical method. It is difficult to determine i_{zi} .

In the paper [1], a probabilistic method is proposed for finding the inertia radius relative to the vertical axis of the car. In the present paper, the formula there exists

$$i_z = \sqrt{\frac{1}{2}ab + \frac{B^2}{12} \pm \frac{1}{6}ab} \quad (5)$$

where a – the projection of the distance from the front axle to the center of mass of the car for the horizontal plane, m; B – automobile track, m.

The authors built a probabilistic model in [2]. The displacement of the centers of mass of the car parts from the front axle and the rear axle in the transverse direction was taken into account. The formula was updated

$$i_z = \sqrt{\left(\frac{1}{2} \pm \frac{1}{6}\right) \left(ab + \frac{B^2 b}{4a}\right)} \quad (6)$$

The results of the experimental determination for the inertia moments and the inertia radius are relative to the vertical axis of the car in [3]. The results are shown for the ten models in Table 1.

In Table 2 estimation of the relative error for determining the mathematical expectation of the inertia radius relative to the vertical axis of the car are shown. The inertia radius relative to the vertical axis defined by the formulas (5) and (6) (in comparison with the experimental results [3]).

The results are shown in Table 2 were established. The relative error for the determination of the inertia radius relative to the vertical axis i_z by the formula (5) is in the range to 14.3–36 %, and according to the revised formula (6) is to 6.83–34.25 %.

Let us define the expression to calculate the error of the inertia moment relative to the vertical axis I_{zc} . It is necessary to relate the error of determining the inertia radius relative to the vertical axis i_z and the inertia moment relative to the vertical axis I_{zc}

$$\begin{aligned} \delta I_{zc} &= \frac{\Delta I_{zc}}{I_{zc}} = \frac{m_a i_z^2 - m_a \bar{i}_z^2}{m_a i_z^2} = 1 - \frac{\bar{i}_z^2}{i_z^2} = \\ &= 1 - \frac{(i_z \pm \Delta i_z)^2}{i_z^2} = \frac{\Delta i_z^2}{i_z^2} \mp 2 \frac{\Delta i_z}{i_z} = \delta i_z^2 \mp 2 \delta i_z, \end{aligned} \quad (7)$$

where ΔI_{zc} , Δi_z – the absolute error in the determination i_z and I_{zc} , respectively.

Table 1 – The results experimental determination of the inertia moments and the inertia radius relative to the vertical axis OZ of the car

The parameters	The cars									
	A	B	C	D	E	F	G	H	I	J
m_a , kg	2 119	2 590	2 178	883	2 050	1 010	795	628	824	1 167
I_{zc} , kg m ²	4 571	6 327	5 435	1 099	5 444	1 030	1 050	481	1 020	2 099
i_z , m	1.469	1.563	1.579	1.115	1.629	1.009	1.149	0.875	1.113	1.341
a , m	1.470	1.680	1.500	0.900	1.490	1.240	1.322	0.863	1.368	1.148
b , m	1.530	1.350	1.550	1.280	1.700	1.020	0.958	1.167	1.012	1.552
L , m	3.000	3.030	3.050	2.180	3.200	2.260	2.280	2.030	2.380	2.700
h , m	0.500	0.500	0.500	0.400	0.500	0.450	0.473	0.421	0.421	0.510
B , m	1.470	1.485	1.570	1.280	1.568	1.107	1.117	0.995	1.166	1.323

Table 2 – Comparison of results for calculation by formulas (5) and (6)

The parameters	The cars									
	A	B	C	D	E	F	G	H	I	J
i_z , m	1.469	1.563	1.579	1.115	1.629	1.009	1.149	0.875	1.113	1.341
\bar{i}_z , m (5)	1.142	1.148	1.170	0.844	1.213	0.857	0.859	0.766	0.897	1.018
\bar{i}_z , m (6)	1.186	1.164	1.217	0.931	1.272	0.871	0.864	0.819	0.904	1.089
$\delta(\bar{i}_z)$, % (5)	28.63	36.16	35.01	32.09	34.29	17.73	33.82	14.30	24.01	31.17
$\delta(\bar{i}_z)$, % (6)	23.86	34.25	29.75	19.73	28.10	15.86	33.01	6.83	23.07	23.10



The largest error δi_{zc} when the lower sign on the right side of expression (7). In this case, when $\delta i_z = 0.35$ value $\delta I_{zc} = 0.82$. In this case, when $\delta i_z = 0.35$ value $\delta I_{zc} = 0.82$. Because it creates more than 80 % of the error to determine the inertia moments relative to the vertical axis δI_{zc} .

The range of variation of the random variable i_z , adopted in [1, 2], is big. Therefore, a large error for a probabilistic method to determine the inertia radius is relative to the vertical axis of the car.

The purpose of the study: improving the accuracy of measurement the inertia radius relative to the vertical axis of the car at the design stage.

To achieve this goal it is necessary to solve the following tasks:

- to offer the calculated dependence, which will allow, at the design stage of the car, to increase the accuracy of determining the inertia radius relative to the vertical axis;
- to assess the adequacy of calculation results to experimental results.

2 Results

2.1 The calculated dependence for determining the inertia radius relative to the vertical axis of the car

Experimental determination of the inertia radius relative to the vertical axis of the car i_z is shown in Table 1. Analysis of the results shows the following. The value i_z is close to the results of the calculation for the inertia radius relative to the vertical axis according to the formula

$$\bar{i}_z = \sqrt{ab} \quad (8)$$

The value i_z is the mean quadratic value of the coordinate a and coordinate b the center of mass of the car. It should be said. Formula (8) was determined by E. A. Chudakov [4] and the following researchers [1, 5, 6]. It is a condition of ensuring the lateral stability of the rear axle of the car at corner entry and exit.

The results of the calculation by the formula (8) given for ten models (those that are shown in Table 1) in Table 3 are shown. The calculated values and the experimental results [3] are compared among themselves.

Shows the following for analysis of the results (given in Table 3). Value of the difference absolute theoretical values and experimental values for the inertia radius relative to the vertical axis of the car calculated by the formula (8) does not exceed 15 %. If we ignore the error for car F and car H. Other 8 cars $|\delta i_z|$ does not exceed 6 %. Given the measurement errors of the inertia radius relative to the vertical axis of the car, for cars A, B, C, D, E, G, I, J, the accuracy of determining the moment of inertia I_{zc} 12 % does not exceed. For car F $\delta I_{zc} = 24$ % and 32 %. For car H – $\delta I_{zc} = 31.33$ %.

To sum up. The accuracy of the calculations increases when the mathematical expectation of the inertia radius relative to the vertical axis of the car about a vertical axis

is used equation (8). The average relative error decreases from 21–27 % to 5 % compared to the calculations on (5) and (6), which was used earlier. This means that the average error of determination for the inertia moments relative to the vertical axis of the car decreased from 46–61 % to 10 %.

Table 4 shows the calculation results for the ratio in the ten car models that were considered. The average value determined.

The average value of the absolute value is the value 0.063, as shows the analysis of the calculation results (Table 4).

S. Litvinov in [5] says: the study of stability and control may be greatly simplified; the inertia radius relative to the vertical axis of the car must be determined in the square, through the product ab , that is, by using the relations (8). M. Julien [7] and A. S. Dobrin [8, 9] did the same. In the paper [5] with reference to the results of the study [6], data characterizing the limits of the relationship for passenger cars different classes. The inertia radius relative to the vertical axis of the car expresses the following relationship

$$\bar{i}_z = A\sqrt{ab} \quad (9)$$

where A – the factor correction that is determined from the ratio

$$A = \frac{i_z}{\sqrt{ab}} \quad (10)$$

In Table 5 shows the values of the parameter A obtained for ten models are given in Table 1.

The parameter A in 42 implementation (given in [5] and Table 5) for estimation of the average value can be used. Two of the car's load (specified in [5]) as the implementation can be used.

As a result, define

$$A = \bar{A} \pm \sigma_A = 0,925 \pm 0,065 \quad (11)$$

where σ_A – the standard deviation of the parameter A .

The calculated value of the inertia radius relative to the vertical axis of the car i_{zcp} within one standard deviation can be determined by the formula

$$A = \bar{A} \pm \sigma_A = 0,925 \pm 0,065 \quad (12)$$

The moment of inertia I_{zcp} relative to the vertical axis of the car estimated value

$$A = \bar{A} \pm \sigma_A = 0,925 \pm 0,065 \quad (13)$$

To convert the expression (13)

$$I_{zcp} = m_a 0,860ab \pm m_a 0,120ab = \bar{I}_{zcp} \pm 0,120m_a ab \quad (14)$$

where \bar{I}_{zcp} – the average value of inertia moment relative to the vertical axis of the car

$$\bar{I}_{zcp} = 0,860m_a ab \quad (15)$$

Table 3 – Comparison of calculation results by formula (8) and the results of the experiment [3]

Parameters	The cars									
	A	B	C	D	E	F	G	H	I	J
$i_z, \text{ m}$	1.469	1.563	1.579	1.115	1.629	1.009	1.149	0.875	1.113	1.341
$\bar{i}_z, \text{ m}$	1.500	1.620	1.525	1.073	1.591	1.125	1.125	1.003	1.177	1.334
$\Delta i_z, \text{ m}$	-0.032	-0.057	0.054	0.042	0.038	-0.116	0.024	-0.128	-0.064	0.007
$\delta i_z, \%$	2.17	3.6	-3.4	-3.8	-2.3	11.5	-2.1	14.6	5.7	0.52
$\delta I_{zc}, \%$	4.39	7.33	6.92	7.74	4.65	24.32	4.24	31.33	11.72	1.04

Table 4 – Results to determine value

Parameters	The cars									
	A	B	C	D	E	F	G	H	I	J
$\bar{i}_z, \text{ m}$	1.500	1.620	1.525	1.073	1.591	1.125	1.125	1.003	1.177	1.334
$\Delta i_z, \text{ m}$	-0.032	-0.057	0.054	0.042	0.038	-0.116	0.024	-0.128	-0.064	0.007
$\left \frac{\Delta i_z}{\bar{i}_z} \right $	0.021	0.035	0.035	0.039	0.024	0.103	0.021	0.128	0.054	0.005
$i_{z\text{max}}, \text{ m}$	1.594	1.722	1.621	1.140	1.691	1.196	1.196	1.066	1.251	1.419
$i_{z\text{min}}, \text{ m}$	1.405	1.518	1.429	1.005	1.491	1.054	1.054	0.940	1.102	1.250
$i_z, \text{ m}$	1.468	1.563	1.579	1.115	1.629	1.009	1.149	0.875	1.113	1.341
average value	0.063									

Table 5 – The parameter A

Parameters	The cars									
	A	B	C	D	E	F	G	H	I	J
$i_z, \text{ m}$	1.469	1.563	1.579	1.115	1.629	1.009	1.149	0.875	1.113	1.341
$\sqrt{ab}, \text{ m}$	1.500	1.620	1.525	1.073	1.591	1.125	1.125	1.003	1.177	1.334
A	0.979	0.965	1.035	1.039	1.024	0.897	1.021	0.872	0.946	1.005

The error relative in determining I_{zcp} within the standard deviation of the inertia radius i_z

$$\delta I_{zcp} = \pm \frac{m_a ab}{I_{zcp}} = \pm \frac{0,12m_a ab}{0,86m_a ab} = \pm 0,139 \quad (16)$$

Data analysis ([5] and Table 5) following. Only 13 implementations outside the interval out of the 42. This is 1 standard deviation of the inertia radius relative to the vertical axis of the car.

2.2 Assessing the adequacy of results for theoretical and experimental studies

The results for theoretical and experimental research are random variables. Make assumption. The data is distributed according to the normal law. We use the quantile for normal distribution of the composition of two random variables – inertia radius for experimental and theoretical by certain [10]

$$u_p = - \left| \frac{\bar{i}_{ze} - \bar{i}_{zp}}{\sqrt{\sigma_e^2 + \sigma_p^2}} \right| \quad (17)$$

where $\bar{i}_{ze}, \bar{i}_{zp}$ – the average value of the inertia radius, defined by experimental and calculated, respectively; σ_e, σ_p – average quadratic error of definition i_{ze} and i_{zp} , respectively.

Table 6 shows the calculation of the quantile up and the probability of a discrepancy between the results of theoretical studies and experimental studies for 10 model car the inertia radius relative to the vertical axis, are given in Table 1.

The calculated value of the standard deviation the inertia radius of the car to the vertical axis

$$\sigma_p = 0,065\sqrt{ab} \quad (18)$$



Table 6 – Assessing the adequacy of the results for determination the inertia radius of the car to the vertical axis, a theoretical way and experimental way

Parameters	The cars									
	A	B	C	D	E	F	G	H	I	J
\bar{l}_{ze} , m	1.469	1.563	1.579	1.115	1.629	1.009	1.149	0.875	1.113	1.341
\bar{l}_{zp} , m	1.387	1.498	1.411	0.992	1.472	1.041	1.041	0.928	1.089	1.234
u_p	-0.421	-0.309	-0.847	-0.882	-0.759	-0.219	-0.738	-0.406	-0.157	-0.617
p	0.660	0.620	0.800	0.810	0.760	0.580	0.770	0.655	0.560	0.730

3 Conclusions

The proposed revised the formula to calculate the inertia radius of the car to the vertical axis at the design stage, which is the result of the study. Using the proposed formula allows to reduce the error in determining the inertia radius from 21–27 % to 5 %.

The accuracy of determining the inertia moment of the car is reduced from 46–61 % to 10 %.

Method for assessing the adequacy of results of theoretical studies and experimental studies, offered by us, showed the following. Using the refined formula for calculating i_z reduces the likelihood of a mismatch results three times.

H

References

1. Podrigalo, M. A., Volkov, V. P., Kyrchatyi, V. Y., & Boboshko, A. A. (2003). Manevrennost' i tormoznye svoystva kolyosnykh mashyn [Maneuverability and Brake Properties of Wheeled Cars]. *KhNADU*. Kharkiv [in Ukrainian].
2. Podrigalo, M. A., Dubinin, E. A., & Glushhenko, V. V. (2015). Utochneniye veroyatnostnogo metoda opredeleniya radiusov inercii kolesnoj mashyny [Clarification of the probabilistic method for determining the radii of inertia of a wheeled car]. *Automobile transport. Collection of scientific works*. No. 37. 116–122 [in Russian].
3. Ellis, D. R. (1975). Upravlyaemost' avtomobilya [Driving ability of the car]. *Moscow. Mashynostroyeniye* [in Russian].
4. Chudakov, E. A. Ustojchivost' avtomobilya pri zanose [Stability of a car with a skidding]. *AN SSSR* [in Russian].
5. Litvinov, A. S. (1971). Upravlyaemost' i ustojchivost' avtomobilya [Controlability and stability of the automobile]. *Moscow. Mashynostroyeniye* [in Russian].
6. Mitschke, M. (1960). Fahrtrichtung und Fahrstabilitat Vor vierradrigen Kraftfahrzeugen. *Deutsche Kraftfahrtforschung*. pp. 135 [in Deutschland].
7. Julien, M. A. (1955). Etude analytique de la stabilite de routes des voitures automobiles. *SJA*. No. 4 [in Italian].
8. Dobrin, A. S. (1966). Issledovaniye dvizheniya avtomobilya po zadannoj traektorii [Investigation of the motion of a car in a given trajectory]. *Proceedings of the workshop on controllability and stability of the car*. No. 1. [in Russian].
9. Dobrin, A. S. (1968). Ustojchivost' i upravlyaemost' avtomobilya pri neustanovivshemsya dvizhenii [Stability and controllability of a car with non-steady motion]. *Automobile industry*. No. 9. 23–27 [in Russian].
10. Podrigalo, M., Isakova, O., & Korobko, A. (2017). Novyy sposib otsinyuvannya zbihu rezul'tativ teoretychnykh i eksperymental'nykh doslidzhen' [A new scientific approach to evaluating the results of research on theoretical and experimental]. *Metrology and instruments. Scientific and production journal*. Vol. 5 (67). 48–51 [in Ukrainian].